

Dimension	Einsatz	Achs- position	Betriebskennung	Profil	Artikel- nummer	EAN	M+S	3PMSF				Bemerkungen	Förderfähigkeit in % (nach Richtlinie 1.3)	Förderfähigkeit in % (nach Richtlinie 1.9)
205/75 R 17.5	Regional	AA	124/122M	BD 200 R	04221530000	4024063002586	X	X	D	C	74 B			0%
205/75 R 17.5	Regional	VA	124/122M	BF 200 R	04121340000	4024063002548	X	X	D	C	71 A			30%
215/75 R 17.5	Regional	AA	126/124M	BD 200 R	04220560000	4024063749184	X	X	D	C	74 B			0%
215/75 R 17.5	Regional	T	135/133K	BT 200 R	05321820000	4024063002234	X		D	C	70 A	Auslauf		30%
215/75 R 17.5	Regional	T	135/133K	BT 300 R	04920750000	4024063005754	X	X	D	C	71 A		100%	30%
215/75 R 17.5	Regional	VA	126/124M	BF 200 R	04121220000	4024063002517	X	X	D	C	71 A			30%
225/75 R 17.5	Regional	AA	129/127M	BD 200 R	04220870000	4024063002562	X	X	D	C	74 B			0%
225/75 R 17.5	Regional	VA	129/127M	BF 200 R	04121250000	4024063002524	X	X	D	C	71 A			30%
235/75 R 17.5	Regional	AA	132/130M	BD 200 R	04221540000	4024063002593	X	X	D	C	74 B			0%
235/75 R 17.5	Regional	T	143/141K (144/144F)	BT 300 R	04920760000	4024063005761	X	X	C	C	70 A		100%	60%
235/75 R 17.5	Regional	VA	132/130M	BF 200 R	04121350000	4024063002555	X	X	D	C	71 A			30%
245/70 R 17.5	Regional	AA	136/134M	BD 200 R	04220880000	4024063002579	X	X	D	C	74 B			0%
245/70 R 17.5	Regional	T	143/141L (146/146F)	BT 300 R	04920770000	4024063005778	X	X	C	C	71 A		100%	60%
245/70 R 17.5	Regional	VA	136/134M	BF 200 R	04121260000	4024063002531	X	X	D	C	71 A			30%
245/70 R 19.5	Regional	AA	136/134M	BD 200 R	05224180000	4024063003477	X	X	E	C	74 B			0%
245/70 R 19.5	Regional	T	141/140K	BT 200 R	05320840000	4024063752450	X		C	C	70 A			60%
245/70 R 19.5	Regional	T	141/140K	BT 300 R	05322560000	4024063005808	X	X				In Vorbereitung	100%	
245/70 R 19.5	Regional	VA	136/134M	BF 200 R	05125900000	4024063003408	X	X	D	B	71 A			30%
245/70 R 19.5	Regional	VA	136/134M	BF 200 R	05128770000	4024063006492	X	X	D	C	71 A	In Vorbereitung		30%
265/70 R 19.5	Regional	AA	140/138M	BD 200 R	05224270000	4024063003484	X	X	D	C	74 B			0%
265/70 R 19.5	Regional	T	143/141J	BT 300 R	05322570000	4024063005792	X	X	C	C	71 A		100%	60%
265/70 R 19.5	Regional	VA	140/138M	BF 200 R	05128800000	4024063006485	X	X	D	C	71 A			30%
285/70 R 19.5	Regional	AA	146/144M	BD 200 R	05224300000	4024063003491	X	X	D	C	76 B			0%
285/70 R 19.5	Regional	T	150/148K	BT 200 R	05320890000	4024063752429	X		C	C	70 A			60%
285/70 R 19.5	Regional	VA	146/144M	BF 200 R	05128850000	4024063006515	X	X	D	C	71 A			30%
445/45 R 19.5	Regional	T	160J	BT 300 R	05322550000	4024063005815	X	X	C	D	72 B		100%	30%
365/80 R 20	Regional	T	160K	NR 52	05323000000	4024063006478			C	D	69 A	In Vorbereitung		60%
13 R 22.5	On- & Off-Road	AA	156/150K	BD 200 M	05225870000	4024063006461	X	X	D	C	75 B			0%
13 R 22.5	On- & Off-Road	AA	156/150K	BD 200 M	05251190000	4024063749733	X	X	D	B	75 B	Auslauf		0%
13 R 22.5	On- & Off-Road	VA	156/150K	BF 200 M	05155620000	4024063003231	X		D	B	71 B			0%
295/80 R 22.5	Regional	AA	152/148M	BD 200 R	05222080000	4024063768574	X	X	D	C	74 B			0%
295/80 R 22.5	Regional	VA	154/149M	BF 200 R	05124710000	4024063002029	X	X	C	B	69 A			60%
315/80 R 22.5	On- & Off-Road	AA	156/150K	BD 200 M	05225850000	4024063006454	X	X	D	C	76 B			0%
315/80 R 22.5	On- & Off-Road	VA	156/150K	BF 200 M	05155130000	4024063002326	X	X	D	B	72 B			0%
315/80 R 22.5	Regional	AA	156/150L (154/150M)	BD 200 R	05221980000	4024063732568	X	X	D	C	75 B			0%
315/80 R 22.5	Regional	VA	156/150L (154/150M)	BF 200 R	05124670000	4024063002067	X	X	C	B	69 A			60%
275/70 R 22.5	Urban	AL	148/145J (151/148E)	BC 31	05140910000	4024063001251	X	X	D	C	71 A		100%	30%
315/70 R 22.5	Regional	AA	154/150L (152/148M)	BD 200 R	05222040000	4024063768536	X	X	D	C	74 B			0%
315/70 R 22.5	Regional	VA	156/150L (154/150M)	BF 200 R	05124680000	4024063002050	X	X	C	B	71 A			60%
385/65 R 22.5	On- & Off-Road	AL	160K	BU 49	05350240000	4024063630321	X		D	C	74 B			0%
385/65 R 22.5	Regional	T	164K	BT 300 R	05322440000	4024063005723	X	X	C	C	70 A	HL	100%	60%
385/65 R 22.5	Regional	VA	160K (158L)	BF 200 R	05124690000	4024063002043	X	X	C	B	73 B			30%
425/65 R 22.5	Regional	T	165K	BT 44	05322940000	4024063006379	X		B	C	70 A			70%

Dimension	Einsatz	Achs- position	Betriebskennung	Profil	Artikel- nummer	EAN	M+S	3PMSF				Bemerkungen	Förderfähigkeit in % (nach Richtlinie 1.3)	Förderfähigkeit in % (nach Richtlinie 1.9)
445/65 R 22.5	On- & Off-Road	T	169K	BS 49	05350230000	4024063630338	X		C	C	73	B		30%
445/65 R 22.5	Regional	T	169K	BT 43	05322930000	4024063006362	X		C	C	73	B		30%
295/60 R 22.5	Regional	AA	150/147L	BD 200 R	05211300000	4024063753051	X	X	D	C	76	B		0%
315/60 R 22.5	Regional	AA	152/148L	BD 200 R	05211280000	4024063753044	X	X	D	C	76	B		0%
315/60 R 22.5	Regional	VA	154/148L	BF 200 R+	05126680000	4024063004412	X	X	C	B	71	A	Auslauf	60%
315/60 R 22.5	Regional	VA	154/148L	BF 200 R+	05128890000	4024063006508	X	X	C	C	71	A		60%
385/55 R 22.5	Regional	T	160K	BT 300 R	05322460000	4024063006447	X	X	B	C	70	A		70%
385/55 R 22.5	Regional	VA	160K (158L)	BF 200 R	05124700000	4024063002036	X	X	C	B	73	B		30%

EU-Laber Viewer: <https://www.barum-tyres.com/transport/services/eu-tyre-label-viewer>

** EU-Labelwerte für Artikel in Vorbereitung werden mit Produktionsstart veröffentlicht.

TT = Tube-Type

VA = Vorderachse, AA = Antriebsachse, T = Trailer

XL/HL = Extra/Heavy Load (erhöhter Last-Index)